

Review

Clean energies for sustainable development and built environment

Abdeen Mustafa Omer

Energy Research Institute (ERI), Forest Road West, Nottingham NG7 4EU, UK
Corresponding Email Address: abdeenomer2@yahoo.co.uk

Abstract

This study highlights the energy problem and the possible savings that can be achieved through the use of renewable energy technologies. Also, this study clarifies the background of the study, highlights the potential energy saving that could be achieved through use of renewable energy technologies and describes the objectives, approach and scope of the study. The move towards a de-carbonised world, driven partly by climate science and partly by the business opportunities it offers, will need the promotion of environmentally friendly alternatives, if an acceptable stabilisation level of atmospheric carbon dioxide is to be achieved. This requires the harnessing and use of natural resources that produce no air pollution or greenhouse gases and provides comfortable coexistence of human, livestock, and plants. The increased availability of reliable and efficient energy services stimulates new development alternatives. We present and focuses on a comprehensive review of energy sources, and the development of sustainable technologies to explore these energy sources. We conclude that using renewable energy technologies, efficient energy systems, energy savings techniques and other mitigation measures is necessary to reduce climate changes.

Keywords: Renewable technologies, energy saving, sustainable development, environment.

INTRODUCTION

Over millions of years ago, the plants have covered the earth, converting the energy of sunlight into living plants and animals, some of which were buried in the depths of the earth to produce deposits of coal, oil and natural gas (Cantrell, and Wepfer, 1984; ASHRAE, 1995; Kavanaugh and Rafferty, 1997). The past few decades, however, have experienced many valuable uses for these complex chemical substances and manufacturing from them plastics, textiles, fertilisers and the various end products of the petrochemical industry. Indeed, each decade seeks increasing uses for these products. Coal, oil and gas, which will certainly be of great value to future generations, as they are to ours, are however non-renewable natural resources. The rapid depletion of these non-renewable fossil resources need not continue. This is particularly true now as it is, or soon will be, technically and economically feasible to supply all of man's needs from the most abundant energy source of all, the sun. The sunlight is not only inexhaustible, but, moreover, it is the only energy source, which is completely non-polluting (UNFCCC, 2009).

Industrial use of fossil fuels has been largely blamed

for warming the climate. When coal, gas and oil are burnt, they release harmful gases, which trap heat in the atmosphere and cause global warming. However, there had been an ongoing debate on this subject, as scientists have struggled to distinguish between changes, which are human induced, and those, which could be put down to natural climate variability. Notably, human activities that emit carbon dioxide (CO₂), the most significant contributor to potential climate change, occur primarily from fossil fuel production. Consequently, efforts to control CO₂ emissions could have serious, negative consequences for economic growth, employment, investment, trade and the standard of living of individuals everywhere. (Abdeen, 2014).

Energy sources and their use

Scientifically, it is difficult to predict the relationship between global temperature and greenhouse gas (GHG) concentrations. The climate system contains many processes that will change if warming occurs. Critical

processes include heat transfer by winds and tides, the hydrological cycle involving evaporation, precipitation, runoff and groundwater and the formation of clouds, snow, and ice, all of which displaying enormous natural variability. The equipment and infrastructure for energy supply and use are designed with long lifetimes, and the premature turnover of capital stock involves significant costs. Economic benefits occur if capital stock is replaced with more efficient equipment in step with its normal replacement cycle. Likewise, if opportunities to reduce future emissions are taken in a timely manner, they should be less costly. Such a flexible approach would allow society to take account of evolving scientific and technological knowledge, while gaining experience in designing policies to address climate change (UNFCCC, 2009).

The World Summit on Sustainable Development in Johannesburg in 2002 (UNFCCC, 2009) committed itself to “encourage and promote the development of renewable energy sources to accelerate the shift towards sustainable consumption and production”. Accordingly, it aimed at breaking the link between resource use and productivity. This can be achieved by the following:

- Trying to ensure economic growth does not cause environmental pollution.
- Improving resource efficiency.
- Examining the whole life-cycle of a product.
- Enabling consumers to receive more information on products and services.
- Examining how taxes, voluntary agreements, subsidies, regulation and information campaigns, can best stimulate innovation and investment to provide cleaner technology.

The energy conservation scenarios include rational use of energy policies in all economy sectors and the use of combined heat and power systems, which are able to add to energy savings from the autonomous power plants. Electricity from renewable energy sources is by definition the environmental green product. Hence, a renewable energy certificate system, as recommended by the World Summit, is an essential basis for all policy systems, independent of the renewable energy support scheme. It is, therefore, important that all parties involved support the renewable energy certificate system in place if it is to work as planned. Moreover, existing renewable energy technologies (RETs) could play a significant mitigating role, but the economic and political climate has to be changed first. It is now universally accepted that climate change is real. It is happening now, and GHGs produced by human activities are significantly contributing to it. The predicted global temperature increase between 1.5 and 4.5°C could lead to potentially catastrophic environmental impacts (United Nations, 2003). These include sea level rise, increased frequency of extreme weather events, floods, droughts, disease migration from various places and possible stalling of the Gulf Stream. This has led scientists to

argue that climate change issues are not ones that politicians can afford to ignore, and policy makers tend to agree (United Nations, 2003). However, reaching international agreements on climate change policies is no trivial task as the difficulty in ratifying the Kyoto Protocol and reaching agreement at Copenhagen have proved.

Therefore, the use of renewable energy sources and the rational use of energy, in general, are the fundamental inputs for any responsible energy policy. However, the energy sector is encountering difficulties because increased production and consumption levels entail higher levels of pollution and eventually climate change, with possibly disastrous consequences. At the same time, it is important to secure energy at an acceptable cost in order to avoid negative impacts on economic growth. To date, renewable energy contributes only as much as 20% of the global energy supplies worldwide (United Nations, 2003). Over two thirds of this comes from biomass use, mostly in developing countries, and some of this is unsustainable. However, the potential for energy from sustainable technologies is huge. On the technological side, renewables have an obvious role to play. In general, there is no problem in terms of the technical potential of renewables to deliver energy. Moreover, there are very good opportunities for RETs to play an important role in reducing emissions of GHGs into the atmosphere, certainly far more than have been exploited so far. However, there are still some technical issues to address in order to cope with the intermittency of some renewables, particularly wind and solar. Nevertheless, the biggest problem with relying on renewables to deliver the necessary cuts in GHG emissions is more to do with politics and policy issues than with technical ones (Bos et al., 1994). For example, the single most important step of governments that could take to promote and increase the use of renewables is to improve access for renewables to the energy market. This access to the market needs to be under favourable conditions and, possibly, under favourable economic rates as well. One move that could help, or at least justify, better market access would be to acknowledge that there are environmental costs associated with other energy supply options and that these costs are not currently internalised within the market price of electricity or fuels. This could make a significant difference, particularly if appropriate subsidies were applied to renewable energy in recognition of the environmental benefits it offers. Similarly, cutting energy consumption through end-use efficiency is absolutely essential. This suggests that issues of end-use consumption of energy will have to come into the discussion in the foreseeable future ones (Bos et al., 1994; Duchin, 1995).

However, RETs have the benefit of being environmentally benign when developed in a sensitive and appropriate way with the full involvement of local communities. In addition, they are diverse, secure, locally based and abundant. In spite of the

enormous potential and the multiple benefits, the contribution from renewable energy still lags behind the ambitious claims for it due to the initially high development costs, concerns about local impacts, lack of research funding and poor institutional and economic arrangements (Duchin, 1995). Hence, an approach is needed to integrate renewable energies in a way that meets the rising demand in a cost-effective way.

Role of efficient energy systems

The prospects for development in power engineering are, at present, closely related to ecological problems. Power engineering has harmful effects on the environment, as it discharges toxic gases into atmosphere and also oil-contaminated and saline waters into rivers, as well as polluting the soil with ash and slag and having adverse effects on living organisms taking into account of electromagnetic fields and so on. Thus there is an urgent need for new approaches to provide an ecologically safe strategy. Substantial economic and ecological effects for thermal power projects (TPPs) can be achieved by improvement, upgrading the efficiency of the existing equipment, reduction of electricity loss, saving of fuel, and optimisation of its operating conditions and service life leading to improved access for rural and urban low-income areas in developing countries through energy efficiency and renewable energies.

Sustainable energy is a prerequisite for development. Energy-based living standards in developing countries, however, are clearly below standards in developed countries. Low levels of access to affordable and environmentally sound energy in both rural and urban low-income areas are therefore a predominant issue in developing countries. In recent years many programmes for development aid or technical assistance have been focused on improving access to sustainable energy, many of them with impressive results. Apart from success stories, however, experience also shows that positive appraisals of many projects evaporate after completion and vanishing of the implementation expert team. Altogether, the diffusion of sustainable technologies such as energy efficiency and renewable energy for cooking, heating, lighting, electrical appliances and building insulation in developing countries has been slow. Energy efficiency and renewable energy programmes could be more sustainable and pilot studies more effective and pulse releasing if the entire policy and implementation process was considered and redesigned from the outset (Givoni, 1998). New financing and implementation processes, which allow reallocating financial resources and thus enabling countries themselves to achieve a sustainable energy infrastructure, are also needed. The links between the energy policy framework, financing and

implementation of renewable energy and energy efficiency projects have to be strengthened and efforts need to be made to increase people's knowledge through training.

Buildings consume energy mainly for cooling, heating and lighting. The energy consumption was based on the assumption that the building operates within ASHRAE-thermal comfort zone during the cooling and heating periods (ASHRAE, 1993). Most of the buildings incorporate energy efficient passive cooling, solar control, photovoltaic, lighting and day lighting, and integrated energy systems. It is well known that thermal mass with night ventilation can reduce the maximum indoor temperature in buildings in summer (Kammerud, Ceballos, Curtis, Place, and Anderson, 1984). Hence, comfort temperatures may be achieved by proper application of passive cooling systems. However, energy can also be saved if an air conditioning unit is used (Shaviv, 1989). The reason for this is that in summer, heavy external walls delay the heat transfer from the outside into the inside spaces. Moreover, if the building has a lot of internal mass the increase in the air temperature is slow. This is because the penetrating heat raises the air temperature as well as the temperature of the heavy thermal mass. The result is a slow heating of the building in summer as the maximal inside temperature is reached only during the late hours when the outside air temperature is already low. The heat flowing from the inside heavy walls could be reduced with good ventilation in the evening and night. The capacity to store energy also helps in winter, since energy can be stored in walls from one sunny winter day to the next cloudy one. However, the admission of daylight into buildings alone does not guarantee that the design will be energy efficient in terms of lighting. In fact, the design for increased daylight can often raise concerns relating to visual comfort (glare) and thermal comfort (increased solar gain in the summer and heat losses in the winter from larger apertures). Such issues will clearly need to be addressed in the design of the window openings, blinds, shading devices, heating system, etc. In order for a building to benefit from daylight energy terms, it is a prerequisite that lights are switched off when sufficient daylight is available. The nature of the switching regime; manual or automated, centralised or local, switched, stepped or dimmed, will determine the energy performance. Simple techniques can be implemented to increase the probability that lights are switched off (Singh, 2000). These include:

- Making switches conspicuous and switching banks of lights independently.
- Loading switches appropriately in relation to the lights.
- Switching banks of lights parallel to the main window wall.

There are also a number of methods, which help reduce the lighting energy use, which, in turn, relate to

the type of occupancy pattern of the building (Singh, 2000). The light switching options include:

- Centralised timed off (or stepped)/manual on.
- Photoelectric off (or stepped)/manual on.
- Photoelectric and on (or stepped), photoelectric dimming.
- Occupant sensor (stepped) on/off (movement or noise sensor).

Likewise, energy savings from the avoidance of air conditioning can be very substantial. Whilst day-lighting strategies need to be integrated with artificial lighting systems in order to become beneficial in terms of energy use, reductions in overall energy consumption levels by employment of a sustained programme of energy consumption strategies and measures would have considerable benefits within the buildings sector. The perception often given however is that rigorous energy conservation as an end in itself imposes a style on building design resulting in a restricted aesthetic solution. It would perhaps be better to support a climate sensitive design approach that encompasses some elements of the pure conservation strategy together with strategies, which work with the local ambient conditions making use of energy technology systems, such as solar energy, where feasible. In practice, low energy environments are achieved through a combination of measures that include:

- The application of environmental regulations and policy.
- The application of environmental science and best practice.
- Mathematical modelling and simulation.
- Environmental design and engineering.
- Construction and commissioning.
- Management and modifications of environments in use.

While the overriding intention of passive solar energy design of buildings is to achieve a reduction in purchased energy consumption, the attainment of significant savings is in doubt. The non-realisation of potential energy benefits is mainly due to the neglect of the consideration of post-occupancy user and management behaviour by energy scientists and designers alike. Calculating energy inputs in agricultural production is more difficult in comparison to the industry sector due to the high number of factors affecting agricultural production, as Table 1 shows. However, considerable studies have been conducted in different countries on energy use in agriculture (CAEEDAC, 2000; Yaldiz et al., 1993; Dutt, 1982; Baruah, 1995; Thakur and Mishra, 1993; Wu and Bogges, 1999) in order to quantify the influence of these factors (Abdeen, 2010; 2011).

Renewable energy technologies

Sustainable energy is the energy that, in its production

or consumption, has minimal negative impacts on human health and the healthy functioning of vital ecological systems, including the global environment. It is an accepted fact that renewable energy is a sustainable form of energy, which has attracted more attention during recent years. Increasing environmental interest, as well as economic consideration of fossil fuel consumption and high emphasis of sustainable development for the future helped to bring the great potential of renewable energy into focus. Nearly a fifth of all global power is generated by renewable energy sources, according to a new book published by the OECD/IEA, (2004). This book entitled "Renewables for power generation: status and prospects" claims that, at approximately 20%, renewables are the second largest power source after coal (39%) and ahead of nuclear (17%), natural gas (17%) and oil (8%) respectively. From 1973-2000 renewables grew at 9.3% a year, and it was predicted that this would increase by 10.4% a year to 2015. Therefore, promoting innovative renewable applications and reinforcing the renewable energy technologies market will contribute to preservation of the ecosystem by reducing emissions at local and global levels. Wind power grew fastest at 52% and should be multiply seven times by 2015, overtaking biopower and hence helping reducing green house gases, GHGs, emissions to the environment. This will also contribute to the amelioration of environmental conditions by replacing conventional fuels with renewable energies that produce no air pollution or greenhouse gases (during their use).

Table 2 shows some applications of different renewable energy sources. The challenge is to match leadership in GHG reduction and production of renewable energy with developing a major research and manufacturing capacity in environmental technologies (wind, solar, fuel cells, etc.). More than 50% of the world's area is classified as arid, representing the rural and desert part, which lack electricity and water networks. The inhabitants of such areas obtain water from borehole wells by means of water pumps, which are mostly driven by diesel engines. The diesel motors are associated with maintenance problems, high running cost, and environmental pollution. Alternative methods are pumping by photovoltaic (PV) or wind systems. At present, renewable sources of energy are regional and site specific. It has to be integrated in the regional development plans.

Solar energy

The availability of data on solar radiation is a critical problem. Even in developed countries, very few weather stations have recorded detailed solar radiation data for a period of time long enough to have statistical significance. Solar radiation arriving on earth is the most fundamental renewable energy source in nature. It

Table 1. Energy equivalent of inputs and outputs (Hall and Scrase, 1998)

Energy source	Unit	Equivalent energy (MJ)
Input		
1. Human labour	h	2.3
2. Animal labour		
Horse	h	10.10
Mule	h	4.04
Donkey	h	4.04
Cattle	h	5.05
Water buffalo	h	7.58
3. Electricity	kWh	11.93
4. Diesel	Litre	56.31
5. Chemicals fertilisers		
Nitrogen	kg	64.4
P ₂ O ₅	kg	11.96
K ₂ O	kg	6.7
6. Seed		
Cereals and pulses	kg	25
Oil seed	kg	3.6
Tuber	kg	14.7
Total input	kg	43.3
Output		
7. Major products		
Cereal and pulses	kg	14.7
Sugar beet	kg	5.04
Tobacco	kg	0.8
Cotton	kg	11.8
Oil seed	kg	25
Fruits	kg	1.9
Vegetables	kg	0.8
Water melon	kg	1.9
Onion	kg	1.6
Potatoes	kg	3.6
Olive	kg	11.8
Tea	kg	0.8
8. By products		
Husk	kg	13.8
Straw	kg	12.5
Cob	kg	18.0
Seed cotton	kg	25.0
Total output	kg	149.04 MJ/kg

Table 2. Sources of renewable energy (Omer, 2007)

Energy source	Technology	Size
Solar energy	• Domestic solar water heaters	Small
	• Solar water heating for large demands	Medium-large
	• PV roofs: grid connected systems generating electric energy	Medium-large
Wind energy	• Wind turbines (grid connected)	Medium-large
Hydraulic energy	• Hydro plants in derivation schemes	Medium-small
	• Hydro plants in existing water distribution networks	Medium-small
Biomass	• High efficiency wood boilers	Small
	• CHP* plants fed by agricultural wastes or energy crops	Medium

Table 2. Continue

Animal manure	•	CHP* plants fed by biogas	Small
CHP (Combined heat and power)	•	High efficiency lighting	Wide
	•	High efficiency electric	Wide
	•	Householders appliances	Wide
	•	High efficiency boilers	Small-medium
	•	Plants coupled with refrigerating machines	Medium-large

powers the bio-system, the ocean and atmospheric current system and affects the global climate. Reliable radiation information is needed to provide input data in modelling solar energy devices and a good database is required in the work of energy planners, engineers, and agricultural scientists. In general, it is not easy to design solar energy conversion systems when they have to be installed in remote locations. First, in most cases, solar radiation measurements are not available for these sites. Second, the radiation nature of solar radiation makes the computation of the size of such systems difficult. While solar energy data are recognised as very important, their acquisition is by no means straightforward. The measurement of solar radiation requires the use of costly equipment such as pyrheliometers and pyranometers. Consequently, adequate facilities are often not available in developing countries to mount viable monitoring programmes. This is partly due to the equipment cost as well as the cost of technical manpower. Several attempts have, however, been made to estimate solar radiation through the use of meteorological and other physical parameter in order to avoid the use of expensive network of measuring instruments (Duffie and Beckman, 1980; Sivkov, 1964a; 1964b; Barabaro et al., 1978; Abdeen, 2010; 2011).

Two of the most essential natural resources for all life on the earth and for man's survival are sunlight and water. Sunlight is the driving force behind many of the RETs. The worldwide potential for utilising this resource, both directly by means of the solar technologies and indirectly by means of biofuels, wind and hydro technologies, is vast. During the last decade interest has been refocused on renewable energy sources due to the increasing prices and fore-seeable exhaustion of presently used commercial energy sources. The most promising solar energy technology are related to thermal systems; industrial solar water heaters, solar cookers, solar dryers for peanut crops, solar stills, solar driven cold stores to store fruits and vegetables, solar collectors, solar water desalination, solar ovens, and solar commercial bakers. Solar photovoltaic PV systems as solar PV for lighting, solar refrigeration to store vaccines for human and animal use, solar PV for water pumping, solar PV for battery chargers, solar PV for communication network, microwave, receiver stations, radio systems in airports, VHF and beacon radio

systems in airports, and educational solar TV posts in villages belong also to solar energy technologies. Solar pumps are most cost effective for low power requirement (up to 5 kW) in remote places. Table 1

Applications include domestic and livestock drinking water supplies, for which the demand is constant throughout the year, and irrigation. However, the suitability of solar pumping for irrigation, though possible, is uncertain because the demand may vary greatly with seasons. Solar systems may be able to provide trickle irrigation for fruit farming, but not usually the large volumes of water needed for wheat growing. Table 2

CHP (Combined heat and power)

The hydraulic energy required to deliver a volume of water is given by the formula:

$$E_w = \rho_w g V H \quad (1)$$

where E_w is the required hydraulic energy (kWh day^{-1}); ρ_w is the water density (kg m^{-3}); g is the gravitational acceleration (ms^{-2}); V is the required volume of water ($\text{m}^3 \text{day}^{-1}$); and H is the head of water (m).

The solar array power required is given by:

$$P_{sa} = E_w / E_{sr} \eta F \quad (2)$$

where: P_{sa} is the solar array peak power (kW_p); E_{sr} is the average daily solar radiation ($\text{kWhm}^{-2} \text{day}^{-1}$); F is the array mismatch factor; and η is the daily subsystem efficiency.

Substituting Eq. (1) in Eq. (2), the following equation is obtained for the amount of water that can be pumped:

$$V = P_{sa} E_{sr} \eta F / \rho_w g H \quad (3)$$

The approximative values, $P_{sa} = 1.6 \text{ kW}_p$, $F = 0.85$, $\eta = 40\%$, may be taken into consideration.

Further increases of PV (photovoltaic systems) depend on the ability to improve the durability, performance and the local manufacturing capabilities of PV.

Biomass

The data required to perform the trade-off analysis simulation of bio-energy resources can be classified according to the divisions given in Table 3, namely the overall system or individual plants, and the existing situation or future development. The effective economical utilisations of these resources are shown in Table 4, but their use is hindered by many problems

Table 3. Classifications of bio-energy resources data requirements (Omer, 2008a)

Criteria	Plant data	System data
Existing data	Size	Peak load
	Life	Load shape
	Cost (fixed and variation operation and maintenance)	Capital costs
	Forced outage	Fuel costs
	Maintenance	Depreciation
	Efficiency	Rate of return
	Fuel	Taxes
	Emissions	
	Future data	All of above, plus
	Capital costs	Fuel price growth
	Construction trajectory	Fuel import limits
	Date in service	Inflation

Table 4. Effective biomass resource utilisation (Omer, 2008b)

Subject	Tools	Constraints
Utilisation and land clearance for agriculture expansion	• Stumpage fees	• Policy
	• Control	• Fuel-wood planning
	• Extension	• Lack of extension
	• Conversion	• Institutional
	• Technology	
Utilisation of agricultural residues	• Briquetting	• Capital
	• Carbonisation	• Pricing
	• Carbonisation and briquetting	• Policy and legislation
	• Fermentation	• Social acceptability
	• Gasification	

such as those related to harvesting, collection, and transportation, besides the photo-sanitary control regulations. Biomass energy is experiencing a surge in interest stemming from a combination of factors e.g greater recognition of its current role and future potential contribution as a modern fuel, global environmental benefits, its development and entrepreneurial opportunities, etc. Possible routes of biomass energy development are shown in Table 5. However, biomass usage and application can generally be divided into the following three categories.

(a) Biomass energy for petroleum substitution driven by the following factors.

- (1) Oil price increase.
 - (2) Balance of payment problems, and economic crisis.
 - (3) Fuel-wood plantations, and residue utilisation.
 - (4) Wood based heat and electricity.
 - (5) Liquid fuels from biomass.
 - (6) Producer gas technology.
- (b) Biomass energy for domestic needs driven by:

- (1) Population increase.
 - (2) Urbanisation.
 - (3) Agricultural expansion.
 - (4) Fuel-wood crisis.
 - (5) Ecological crisis.
 - (6) Fuel-wood plantations, agro-forestry.
 - (7) Community forestry, and residue utilisation.
 - (8) Improved stoves, and improved charcoal production.
- (c) Biomass energy for development driven by
- (1) Electrification.
 - (2) Irrigation and water supply.
 - (3) Economic and social development.
 - (4) Fuel-wood plantations.
 - (5) Community forestry.
 - (6) Agro-forestry.
 - (7) Briquettes.
 - (8) Producer gas technology.

The use of biomass through direct combustion has long been, and still is, the most common mode of biomass utilisation (Table 5). Examples for dry

Table 5. Agricultural residues routes for development (Omer, 2008c)

Source	Process	Product	End use
Agricultural, and animal residues	Direct	Combustion	(Save or less efficiency as wood)
	Briquettes	Direct combustion	(Similar end use devices or improved)
	Carbonisation	Carbonised	Use
	Carbonisation	Briquettes	Briquettes use
	Fermentation	Biogas	Use

(thermo-chemical) conversion processes are charcoal making from wood (slow pyrolysis), gasification of forest and agricultural residues (fast pyrolysis – this is still in demonstration phase), and of course, direct combustion in stoves, furnaces, etc. Wet processes require substantial amount of water to be mixed with the biomass. Biomass technologies include:

- Carbonisation and briquetting.
- Improved stoves.
- Biogas.
- Improved charcoal.
- Gasification.

Briquetting and Carbonisation

Briquetting is the formation of a charcoal (an energy-dense solid fuel source) from otherwise wasted agricultural and forestry residues. One of the disadvantages of wood fuel is that it is bulky with a low energy density and therefore requires transport. Briquette formation allows for a more energy-dense fuel to be delivered, thus reducing the transportation cost and making the resource more competitive. It also adds some uniformity, which makes the fuel more compatible with systems that are sensitive to the specific fuel input. Charcoal stoves are very familiar to African societies. As for the stove technology, the present charcoal stove can be used, and can be improved upon for better efficiency. This energy term will be of particular interest to both urban and rural households and all the income groups due to its simplicity, convenience, and lower air polluting characteristics. However, the market price of the fuel together with that of its end-use technology may not enhance its early high market penetration especially in the urban low income and rural households.

Charcoal is produced by slow heating wood (carbonisation) in airtight ovens or retorts, in chambers with various gases, or in kilns supplied with limited and controlled amounts of air. The charcoal yield decreased gradually from 42.6 to 30.7% for the hazelnut shell and from 35.6 to 22.7% for the beech wood with an increase of temperature from 550 to 1,150 K

while the charcoal yield from the lignin content decreases sharply from 42.5 to 21.7% until it was at 850 °K during the carbonisation procedures (Barabaro et al., 1978; Abdeen, 2009; 2010; 2011). The charcoal yield decreases as the temperature increases, while the ignition temperature of charcoal increases as the carbonisation temperature increases. The charcoal briquettes that are sold on the commercial market are typically made from a binder and filler.

Dry cell batteries are a practical but expensive form of mobile fuel that is used by rural people when moving around at night and for powering radios and other small appliances. The high cost of dry cell batteries is financially constraining for rural households, but their popularity gives a good indication of how valuable a versatile fuel like electricity is in rural areas (Table 6). However, dry cell batteries can constitute an environmental hazard unless they are recycled in a proper fashion. Tables (6 and 7) further show that direct burning of fuel-wood and crop residues constitute the main usage of biomass, as is the case with many developing countries. In fact, biomass resources play a significant role in energy supply in all developing countries. However, the direct burning of biomass in an inefficient manner causes economic loss and adversely affects human health. In order to address the problem of inefficiency, research centres around the world, e.g., (Hall and Scrase, 1998) have investigated the viability of converting the resource to a more useful form of improved charcoal, namely solid briquettes and fuel gas. Accordingly, biomass resources should be divided into residues or dedicated resources, the latter including firewood and charcoal can also be produced from forest residues (Table 7). Whichever form of biomass resource used, its sustainability would primarily depend on improved forest and tree management.

Improved cook stoves

Traditional wood stoves are commonly used in many rural areas. These can be classified into four types:

Table 6. Energy carrier and energy services in rural areas (Omer, 2009)

Energy carrier	Energy end-use
Fuel-wood	Cooking
	Water heating
	Building materials
	Animal fodder preparation
Kerosene	Lighting
	Ignition fires
Dry cell batteries	Lighting
	Small appliances
Animal power	Transport
	Land preparation for farming
	Food preparation (threshing)
Human power	Transport
	Land preparation for farming
	Food preparation (threshing)

Table 7. Biomass residues and current use (Omer, 2010)

Type of residue	Current use
Wood industry waste	Residues available
Vegetable crop residues	Animal feed
Food processing residue	Energy needs
Sorghum, millet, wheat residues	Fodder, and building materials
Groundnut shells	Fodder, brick making, direct fining oil mills
Cotton stalks	Domestic fuel considerable amounts available for short period
Sugar, bagasse, molasses	Fodder, energy need, ethanol production (surplus available)
Manure	Fertiliser, brick making, plastering

three stone, metal cylindrical shaped, metal tripod and clay type. Indeed, improvements of traditional cookers and ovens to raise the efficiency of fuel saving can secure rural energy availability, where woody fuels have become scarce. However, planting fast growing trees to provide a constant fuel supply should also be considered. The rural development is essential and economically important since it will eventually lead to a better standard of living, people's settlement, and self-sufficiency (Abdeen, 2009; 2010; 2011).

Biogas

Biogas technology cannot only provide fuel, but is also important for comprehensive utilisation of biomass forestry, animal husbandry, fishery, agricultural economy, protecting the environment, realising agricultural recycling as well as improving the sanitary conditions, in rural areas. However, the introduction of biogas technology on a wide scale has implications for macro planning such as the allocation of government

investment and effects on the balance of payments. Hence, factors that determine the rate of acceptance of biogas plants, such as credit facilities and technical backup services, are likely to have to be planned as part of general macro-policy, as do the allocation of research and development funds (Hall and Scrase, 1998; Abdeen, 2009; 2010; 2011).

Gasification

Gasification is based on the formation of a fuel gas (mostly CO and H₂) by partially oxidising raw solid fuel at high temperatures in the presence of steam or air. The technology can use wood chips, groundnut shells, sugar cane bagasse, and other similar fuels to generate capacities from 3 kW to 100 kW. Many types of gasifier designs have been developed to make use of the diversity of fuel inputs and to meet the requirements of the product gas output (degree of cleanliness, composition, and heating value) (Hall and Scrase, 1998; Abdeen, 2009; 2010; 2011).

Table 8. Final energy projections including biomass (metric ton of equivalent 'Mtoe') (Abdeen, 2011)

Region	2011			
	Biomass	Conventional Energy	Total	Share of Biomass (%)
Africa	205	136	341	60
China	206	649	855	24
East Asia	106	316	422	25
Latin America	73	342	416	18
South Asia	235	188	423	56
Total developing countries	825	1632	2456	34
Other non-OECD countries	24	1037	1061	1
Total non-OECD countries	849	2669	3518	24
OECD countries	81	3044	3125	3
World	930	5713	6643	14
Region	2020			
	Biomass	Conventional Energy	Total	Share of Biomass (%)
Africa	371	266	631	59
China	224	1524	1748	13
East Asia	118	813	931	13
Latin America	81	706	787	10
South Asia	276	523	799	35
Total developing countries	1071	3825	4896	22
Other non-OECD countries	26	1669	1695	1
Total non-OECD countries	1097	5494	6591	17
OECD countries	96	3872	3968	2
World	1193	9365	10558	11

Biomass and sustainability

A sustainable energy system includes energy efficiency, energy reliability, energy flexibility, fuel poverty, and environmental impacts. A sustainable biofuel has two favourable properties, which are availability from renewable raw material, and its lower negative environmental impact than that of fossil fuels. Global warming, caused by CO₂ and other substances, has become an international concern in recent years. To protect forestry resources, which act as major absorbers of CO₂, by controlling the ever-increasing deforestation and the increase in the consumption of wood fuels, such as firewood and charcoal, is therefore an urgent issue. Given this, the development of a substitute fuel for charcoal is necessary. Briquette production technology, a type of clean coal technology, can help prevent flooding and serve as a global warming countermeasure by conserving forestry resources through the provision of a stable supply of briquettes as a substitute for charcoal and firewood.

There are many emerging biomass technologies with large and immediate potential applications, e.g., biomass gasifier/gas turbine (BGST) systems for power generation with pilot plants, improved techniques for

biomass harvesting, transportation and storage. Gasification of crop residues such as rice husks, groundnut shells, etc., with plants already operating in China, India, and Thailand. Treatment of cellulosic materials by steam explosion which may be followed by biological or chemical hydrolysis to produce ethanol or other fuels, cogeneration technologies, hydrogen from biomass, striling energies capable of using biomass fuels efficiently, etc. Table 8 gives a view of the use of biomass and its projection worldwide.

However, a major gap with biomass energy is that research has usually been aimed at obtaining supply and consumption data, with insufficient attention and resources being allocated to basic research, to production, harvesting and conservation processes. Biomass has not been closely examined in terms of a substitute for fossil fuels compared to carbon sequestration and overall environmental benefits related to these different approaches. To achieve the full potential of biomass as a feedstock for energy, food, or any other use, requires the application of considerable scientific and technological inputs (Hall, and Scrase, 1998; Pernille, 2004). However, the aim of any modern biomass energy systems must be:

- (1) To maximise yields with minimum inputs.
- (2) Utilise and select adequate plant materials and processes.
- (3) Optimise use of land, water, and fertiliser.
- (4) Create an adequate infrastructure and strong RandD base.

An afforestation programme appears an attractive option for any country to pursue in order to reduce the level of atmospheric carbon by enhancing carbon sequestration in the nation's forests, which would consequently mitigate climate change (Omer, 2011). However, it is acknowledged that certain barriers need to be overcome if the objectives are to be fully achieved. These include the followings.

- Low level of public awareness of the economic/environmental benefits of forestry.
- The generally low levels of individuals' income.
- Pressures from population growth.
- The land tenural system, which makes it difficult (if at all possible) for individuals to own or establish forest plantations.
- Poor pricing of forest products especially in the local market.
- Inadequate financial support on the part of governments.
- Weak institutional capabilities of the various Forestry Departments as regards technical manpower to effectively manage tree plantations.

However, social policy conditions are also critical. This is still very much lacking particularly under developing countries conditions. During the 1970s and 1980s different biomass energy technologies were perceived in sub-Saharan Africa as a panacea for solving acute problems. On the account of these expectations, a wide range of activities and projects were initiated. However, despite considerable financial and human efforts, most of these initiatives have unfortunately been a failure. Table 8 gives a view of the use of biomass in 2011 compared to 2020 projection.

Therefore, future research efforts should concentrate on the following areas.

- Directed R and D activities in the most promising areas of biomass to increase energy supply and to improve the technological base.
- Formulate a policy framework to encourage entrepreneurial and integrated process.
- Pay more attention to sustainable production and use of biomass energy feedstocks, methodology of conservation and efficient energy flows.
- More research aimed at pollution abatement.
- Greater attentions to interrelated socio-economic aspects.
- Support R and D activities on energy efficiency in production and use.
- Improve energy management skills and take maximum advantage of existing local knowledge.

- Closely examine past successes and failures to assist policy makers with well-informed recommendations.

CONCLUSIONS

There is strong scientific evidence that the average temperature of the earth's surface is rising. This is a result of the increased concentration of carbon dioxide and other GHGs in the atmosphere as released by burning fossil fuels. This global warming will eventually lead to substantial changes in the world's climate, which will, in turn, have a major impact on human life and the built environment. Therefore, effort has to be made to reduce fossil energy use and to promote green energy, particularly in the building sector. Energy use reductions can be achieved by minimising the energy demand, rational energy use, recovering heat and the use of more green energy. This study was a step towards achieving this goal.

REFERENCES

- Abdeen MO (2014). "Clean energies for sustainable development and built environment", *International Journal of Environmental Science and Toxicology*, Vol.2, No.2, p.1-12, 2014.
- Abdeen MO (2008a). "People, power and pollution", *Renewable and Sustainable Energy Reviews*, Vol.12 No.7, p.1864-1889, United Kingdom, September 2008.
- Abdeen MO (2009). "Chapter 3: Energy use, environment and sustainable development", In: *Environmental Cost Management*, Editors: Randi Taylor Mancuso, 2009 NOVA Science Publishers, Inc., p.129-166, New York, USA, 2009.
- Abdeen MO (2011). "Energy and environment: applications and sustainable development", *British Journal of Environment and Climate Change*, Vol.1, No.3, p.118-158, England, September 2011.
- Abdeen MO (2007). "Chapter 6: Energy, water and sustainable development", In: *Focus on Sustainable Development Research Advances*, Editor: Barton A. Larson, 2007 NOVA Science Publishers, Inc., p.189-205, New York, USA, 2007.
- Abdeen MO (2008c). "Green energies and the environment", *Renewable and Sustainable Energy Reviews*, 12 (2008) 1789-1821.
- Abdeen MO (2010). "A review of non-conventional energy systems and environmental pollution control", *International Journal of Environmental Engineering*, Vol.1, No.7, p.127-154, Nigeria, December 2010.
- ASHRAE (1993). "Energy efficient design of new building except new low-rise residential buildings", BSRIASHRAE proposed standards 90-2P-1993, alternative GA: American Society of Heating, Refrigerating, and Air Conditioning Engineers Inc., USA, 1993.
- ASHRAE (1995). "Commercial/Institutional Ground Source Heat Pump Engineering Manual. American Society of heating, Refrigeration and Air-conditioning Engineers", Inc. Atlanta, GA: USA.
- Barabaro S, Coppolino S, Leone C, Sinagra E (1978). "Global solar radiation in Italy", *Solar Energy* 1978; 20: 431-38.
- Baruah D (1995). "Utilisation pattern of human and fuel energy in the plantation", *Journal of Agriculture and Soil Science* 1995; 8(2): 189-92.
- Bos E, My T, Vu E, Bulatao R (1994). "World population projection: 1994-95", Baltimore and London: World Bank by the John Hopkins University Press; 1994.
- CAEEDAC (2000). "A descriptive analysis of energy consumption in

- agriculture and food sector in Canada”, Final Report, February 2000.
- Cantrell J, Wepfer W (1984). “Shallow Ponds for Dissipation of Building Heat: A case Study”, ASHRAE Transactions 90 (1): 239-246.
- D'Apote SL (1998) “IEA biomass energy analysis and projections”, In: Proceedings of Biomass Energy Conference: Data, analysis and Trends, Paris: OECD; 23-24 March 1998.
- Duchin F (1995). “Global scenarios about lifestyle and technology, the sustainable future of the global system”, Tokyo: United Nations University; 1995.
- Duffie JA, Beckman WA (1980). “Solar Engineering of Thermal Processes”, New York: J. Wiley and Sons; 1980.
- Dutt B (1982). “Comparative efficiency of energy use in rice production”, Energy 1982; 6:25.
- Givoni B (1998). “Climate consideration in building and urban design”, New York: Van Nostrand Reinhold; 1998.
- Hall O, Scrase J (1998). “Will biomass be the environmentally friendly fuel of the future?”, Biomass and Bioenergy 1998; 15: 357-67.
- Kammerud R, Ceballos E, Curtis B, Place W, Anderson B (1984) “Ventilation cooling of residential buildings”, ASHRAE Trans: 90 Part 1B, 1984.
- Kavanaugh S, Rafferty K (1997). “Ground source heat pumps. Design of Geothermal Systems for Commercial and Institutional Buildings”, American Society of heating, Refrigeration and Air-conditioning Engineers, Inc. Atlanta, GA: USA.
- OECD/IEA (2004). “Renewables for power generation: status and prospect”, UK, 2004.
- Omer AM (2008b). “Energy, environment and sustainable development”, Renewable and Sustainable Energy Reviews, Vol.12, No.9, p.2265-2300, United Kingdom, December 2008.
- Pernille M (2004). “Feature: Danish lessons on district heating”, (2004), Energy Resource Sustainable Management and Environmental March/April 2004: 16-17.
- Rees WE (1999). “The built environment and the ecosphere: a global perspective”, Building Research and information 1999; 27(4): 206-20.
- Shaviv E (1989). “The influence of the thermal mass on the thermal performance of buildings in summer and winter”, In: Steemers TC, Palz W., editors. Science and Technology at the service of architecture, Dordrecht: Kluwer Academic Publishers, 1989, p. 470-2.
- Singh J (2000). “On farm energy use pattern in different cropping systems in Haryana”, India, Germany: International Institute of Management-University of Flensburg, Sustainable Energy Systems and Management, Master of Science; 2000.
- Sivkov SI (1964a). “To the methods of computing possible radiation in Italy”, Trans. Main Geophys. Obs. 1964; 160.
- Sivkov SI (1964b). “On the computation of the possible and relative duration of sunshine”, Trans. Main Geophys Obs 160. 1964.
- Thakur C, Mistra B (1993). “Energy requirements and energy gaps for production of major crops in India”, Agricultural Situation of India 1993; 48: 665-89.
- The United Nations Framework Convention on Climate Change (UNFCCC). (2009). “The draft of the Copenhagen Climate Change Treaty”, p. 3-181.
- United Nations (2003). “World urbanisation project: the 2002 revision”, New York: The United Nations Population Division.
- Wu J, Boggess W (1999). “The optimal allocation of conservation funds”, Journal Environmental Economic Management. 1999; 38.
- Yaldiz O, Ozturk H, Zeren Y (1993). “Energy usage in production of field crops in Turkey”, In: 5th International Congress on Mechanisation and Energy Use in Agriculture. Turkey: Kusadasi; 11-14 October 1993.

How to cite this article: Abdeen MO (2014). Clean energies for sustainable development and built environment. Int. J. Environ. Sci. Toxic. Res. Vol. 2(2):24-35