

Evaluation of the Application of BIM Technology Based on PCA - Q Clustering Algorithm and Choquet Integral

Wei Xiaozhao, Hong Wenxia, Yang Fan, Jiang Zhenyao

(Qingdao University of Technology, Qingdao, Shandong 266520)

Keywords: PCA—QClustering; Choquet integral ; BIM Technology

Abstract. For the development of the construction industry, the construction of data era is approaching, BIM (building information model) with the actual needs of the construction industry has been widely used as a building information system software, different software for the practical application of different maturity, through the expert scoring method for the application of BIM technology maturity index mark, establish the evaluation index system, using PCA - Q clustering algorithm for the evaluation index system of classification, comprehensive evaluation in combination with the Choquet integral on the classification of evaluation index system, to achieve a reasonable assessment of the application of BIM technology maturity index. To lay a foundation for the future development of BIM Technology in various fields of construction, at the same time provides direction for the comprehensive application of BIM technology.

0 Preface

Since China entered the twenty-first Century, the rapid development of economic construction, with the increasing progress of economy, the construction industry chain has been a huge influence, building the application of information technology has also been a good development, BIM technology is a cutting-edge technology of global construction of information technology in our country, the promotion of the development of BIM technology has attracted much attention and has been applied in the actual construction project with his family thought, but the BIM technical information structure is huge, there is no guarantee that all software can be applied to practical engineering, the application of BIM technology maturity evaluation is conducive to the development of BIM technology and improvement, can make more practical application of BIM technology direct, strengthen the promotion of BIM technology, indirectly provides the direction for the development of BIM technology.

1 Overview of application of BIM Technology

Under the trend of global economic society, industrialization, industrialization, the increasingly close relationship between the information and information factors become economic and social development is one of the important factors. BIM technology architecture exhibition industry, information technology, as the core will become increasingly comprehensive development to adapt to the needs of the actual engineering, the engineering project in BIM Technology of collaborative

management more convenient and efficiency, the management of BIM technology will be closely integrated project specific technical level and management level, the combination of tools and techniques to project whole life cycle management, reasonable and effective control of engineering project in the various stages of the operation, to ensure smooth operation of each project.

2 Classification of PCA application maturity evaluation index based on Q - BIM clustering algorithm

By the experts on the BIM technology application maturity evaluation index system for scoring, each index is composed of 10 factors, the table is as follows: 1:

From table 1 shows, each level indicator is viewed as a 10 dimensional vector, a total of 18 10 dimensional vector consisting of high-dimensional data sets, in order to ensure the rationality of the data classification, principal component analysis method and Q type clustering combination method, the screened reasonable data group to the overall response number according to the characteristics. The method through the PCA of indicators for dimensionality reduction, low dimensional embedding data expressed as data manifold linear smoothing function combination, Q type clustering algorithm was then used to reduce the dimension of the data set, cluster analysis was conducted, and the index system of reasonable classification.

1) Standardized processing of raw data^[2-5]

When the principal component analysis is carried out, the dimension of the index is often different, so the influence of the dimension should be eliminated before the principal component is calculated^[6-8]. Standardization of raw data transform are as follows:

$$x_{ij}^* = \frac{x_{ij} - \bar{x}_j}{s_j} \quad i = 1, 2, \dots, n; j = 1, 2, \dots, p \quad (1)$$

Among:

$$\bar{x}_j = \frac{1}{n} \sum_{i=1}^n x_{ij}, \quad s_j^2 = \frac{1}{n-1} \sum_{i=1}^n (x_{ij} - \bar{x}_j)^2$$

2) Computing covariance matrix

$$\Sigma = (s_{ij})_{p \times p}, \text{among} \quad (2)$$

$$s_{ij} = \frac{1}{n-1} \sum_{k=1}^n (x_{ki} - \bar{x}_i)(x_{kj} - \bar{x}_j) \quad i, j = 1, 2, \dots, p$$

Table 1 BIM application maturity evaluation index score

| index | Factor 1 | Factor 2 | Factor 3 | Factor 4 | Factor 5 | Factor 6 | Factor 7 | Factor 8 | Factor 9 | Factor 10 |
|--|----------|----------|----------|----------|----------|----------|----------|----------|----------|-----------|
| Data completeness and availability | 85 | 80 | 82 | 85 | 82 | 83 | 82 | 81 | 85 | 86 |
| Data mutual | 86 | 84 | 80 | 90 | 83 | 82 | 84 | 82 | 83 | 84 |
| Conflict detection capability | 85 | 83 | 82 | 90 | 84 | 81 | 83 | 80 | 80 | 80 |
| information content | 84 | 84 | 84 | 91 | 81 | 80 | 80 | 82 | 83 | 85 |
| Support professional | 82 | 85 | 83 | 93 | 82 | 81 | 82 | 80 | 82 | 83 |
| Spatial localization ability | 80 | 83 | 84 | 85 | 84 | 85 | 83 | 81 | 90 | 90 |
| Hardware capability | 90 | 85 | 83 | 83 | 85 | 82 | 80 | 0 | 0 | 0 |
| Timeliness of information transmission | 95 | 87 | 82 | 84 | 81 | 85 | 81 | 84 | 80 | 82 |
| Access control | 90 | 83 | 81 | 86 | 81 | 87 | 83 | 82 | 80 | 0 |
| Change management and Application | 88 | 82 | 87 | 82 | 84 | 80 | 86 | 81 | 83 | 85 |
| life cycle | 80 | 80 | 84 | 0 | 83 | 83 | 81 | 0 | 0 | 0 |
| Business information flow | 84 | 80 | 85 | 85 | 83 | 82 | 82 | 81 | 84 | 86 |
| Basic equipment | 86 | 0 | 84 | 0 | 83 | 81 | 81 | 0 | 0 | 0 |
| Human resource management | 84 | 83 | 85 | 82 | 84 | 82 | 80 | 82 | 80 | 81 |
| Product based, service oriented | 89 | 84 | 83 | 82 | 84 | 81 | 83 | 82 | 80 | 82 |
| Contract system | 84 | 85 | 83 | 80 | 83 | 0 | 0 | 0 | 0 | 0 |
| Regulation | 83 | 84 | 81 | 81 | 84 | 0 | 0 | 0 | 0 | 0 |
| Reserve forces | 85 | 82 | 80 | 82 | 81 | 0 | 0 | 0 | 0 | 0 |

3) Find the eigenvalues of the covariance matrix λ_i Characteristic vectors after orthogonal variation a_i

Covariance matrix m Characteristic value of a feature vector $\lambda_1 \geq \lambda_2 \geq \lambda_3 \dots \lambda_m > 0$, Just

before m Variance values corresponding to the principal components., λ_i Corresponding unit feature

vector a_i Principal component F_i On the coefficient of the original variable, The original variable No. i Principal component score F_i by:

$$F_i = a_i X \quad (3)$$

Variance (information) contribution rate of principal component is used to reflect the size of information, α_i by:

$$\alpha_i = \lambda_i / \sum_{i=1}^m \lambda_i \quad (4)$$

4) Select principal component

Finally to select a few main components, That is F_1, F_2, \dots, F_m in m Is determined by the variance (information) cumulative contribution rate $G(m)$ To determine.

$$G(m) = \sum_{i=1}^m \lambda_i / \sum_{k=1}^p \lambda_k \quad (5)$$

When the principal component is worth the cumulative contribution rate of more than 85%, it can be found that the performance of the initial variables can be reflected by the information.

5) Calculate principal component load

Principal component loading is a reflection of the principal component scores F_i with Initial variable X_j The close degree, Initial variable $X_j (j = 1, 2, \dots, p)$ In each main score $F_i (i = 1, 2, \dots, m)$ Load in $l_{ij} (i = 1, 2, \dots, m; j = 1, 2, \dots, p)$:

$$l(Z_i, X_j) = \sqrt{\lambda_i} a_{ij} (i = 1, 2, \dots, m; j = 1, 2, \dots, p) \quad (6)$$

6) Principal component score

Calculate sample in m Score on a principal component:

$$F_i = a_{1i} X_1 + a_{2i} X_2 + \dots + a_{pi} X_p \quad i = 1, 2, \dots, m \quad (7)$$

Solving model:

Using Matlab programming, the 8 main components, the cumulative contribution rate reached 91.22%, can be clearly seen as the main component of the filter has a strong representative and reasonable.

Table 2 principal component analysis

| Principal component category | Characteristic value | Individual contribution rate | Cumulative contribution rate |
|--|----------------------|------------------------------|------------------------------|
| Data completeness and availability | 54.445 | 54.445 | 54.445 |
| Conflict detection capability | 7.407 | 7.407 | 61.852 |
| information content | 6.182 | 6.182 | 68.034 |
| Hardware capability | 6.041 | 6.041 | 74.075 |
| Timeliness of information transmission | 5.351 | 5.351 | 78.425 |
| Change management system | 4.645 | 4.645 | 83.070 |
| Business information flow | 4.416 | 4.416 | 87.487 |
| Product based service | 3.732 | 3.732 | 91.219 |

By using the Q clustering algorithm to classify the principal components, the specific steps are as follows:

- 1) set up $\Omega = \{w_1, w_2, w_3, \dots, w_{12}\}$, Calculate the distance between 8 sample points d_{ij} , Record as a matrix $D = (d_{ij})_{n \times n}$, $d(x, y) = [\sum_{k=1}^p |x_k - y_k|^2]^{\frac{1}{2}}$;
- 2) The preparation of 8 kinds of data, each class contains only one sample point, all kinds of platform height is 0;
- 3) The nearest two class is a new class, and the distance between the two classes is the height of the platform;
- 4) Calculate the distance between the new class and other types of values, if the class number is equal to 1, the transfer step (5), not equal to 1 when the return to the step (3);
- 5) Determines the number and class of classes.

Table 3 results of cluster analysis

| | | | | | | | | |
|---------------------|--------------------------------|-------------------------------|---------------------|---------------------|------------------------------------|-------------------|----------------|-----------------------|
| principal component | Data abundance and reliability | Conflict detection capability | information content | Hardware capability | Real-time information transmission | Change management | operation flow | Products and services |
| category | 1 | 2 | 2 | 1 | 1 | 2 | 2 | 1 |

3 Evaluation of principal component index by Choquet fuzzy integral

Combined with BIM technology application maturity index, index factors, the main factor as a fuzzy aggregation operator, using Choquet fuzzy integral, Its definition is as follows: Set a finite set $Y = \{y_1, y_2, y_3, \dots, y_{n-1}, y_n\}$, the function is defined as the $Y(x)$ discrete function, and the function value is $\{y(x_1), y(x_2), y(x_3), \dots, y(x_{n-1}), y(x_n)\}$, The assumption function $y(x)$ is monotone increasing, That is $y(x_1) \leq y(x_2) \leq y(x_3) \dots y(x_{n-1}) \leq y(x_n)$, Then define $^{[11]}Y(x)$ in the X on the fuzzy measure of the Choquet fuzzy integral:

$$\int_X \mu(x) d\rho = \sum_{i=1}^n \rho(A_i) [y(x_i) - y(x_{i-1})], \text{integral form: } y(x_0) = 0, A_i = \{x_i, x_{i+1}, \dots, x_n\} \quad (10)$$

Choquet is an extension of weighted average operator.

The above fuzzy integral can be used to sort the dominant elements in order to get the final BIM technology application maturity sort, and the application effect of BIM technology to complete the comprehensive evaluation. Sort results are shown in table 4:

Table 4 main component index sort results

| principal component | category | sort |
|------------------------------------|----------|------|
| Data abundance and reliability | 1 | 3 |
| Conflict detection capability | 2 | 2 |
| information content | 2 | 4 |
| Hardware capability | 1 | 6 |
| Real-time information transmission | 1 | 1 |
| Change management | 2 | 5 |
| operation flow | 2 | 7 |
| Products and services | 1 | 8 |

4 Conclusion

This paper introduces the concept of BIM technology application, reference to the United States on the application of BIM technology maturity standards^[12], In accordance with the principle of scientific rationality grading on the application of BIM Technology Maturity, and gives the application of BIM Technology mature degree index system, according to the expert's score, using PCA-Q type clustering algorithms for data processing, classification, combination of Choquet fuzzy integral derived the principal component (indicators) sort, direct reflect the maturity of the application of BIM Technology gap, for the future development of the technology and application of Bim and provide convenience.

reference:

- [1] He Guanpei. What's that thing called BIM.[M],Beijing: China Building Industry Press, 2012:56—58.
- [2] Cao Fuyuan. Research on clustering algorithm for categorical data[D].Taiyuan:Shanxi University,2010.
- [3] Wang Lili. Spectral clustering algorithm[D].Zhengzhou:Henan University,2012.
- [4]Zhou Lin, Xu Sen, Ping Xi Jian, Zhang Tao. Integrated clustering algorithm based on spectral clustering[J]. Journal of automation,2012,08:1335-1342.
- [5]Xu Xiaoli. Research on image segmentation algorithm based on clustering analysis[D].Harbin Engineering University,2012.
- [6]Ding Shifei, Jia Hongjie, the history of Zhongzhi.Adaptive clustering algorithm for large data Nystr spectrum based on M sampling [J]. Journal of software,2014,09:2037-2049.
- [7]Zhang Yaping. Spectral clustering algorithm and its application[D].North Central University,2014.
- [8]Lin Li, pan insurance. The wind farm cluster partition method split hierarchy clustering algorithm based on semi supervised spectral[J]. Electric power automation equipment,2015,02:8-14.
- [9]Li Yong, Changsheng tube. Information management mode and strategy of engineering project based on BIM Technology[J]. Journal of Engineering Management,2012,04:17-21.
- [10]Wu Shuangyue. Research on information classification and coding system of architecture based on BIM[D].Beijing Jiaotong University,2015.
- [11]Huang Jie, Li Bicheng, Zhao Yongjun. Target threat assessment method based on fuzzy integral Choquet [J],2012,13(1).18—21.
- [12]Sun Chengshuang, Jiang Fan, Man Qingpeng. A review of the application of BIM technology in the construction industry[J].Journal of Engineering Management ,2014,03:27-31.

Author introduction:

Wei Xiaozhao (1991-), male, graduate student. Research direction: Civil Engineering and engineering cost management. Work unit: Qingdao Technological University.

Hong Wenxia (1964-), female, master's degree. Title: Qingdao Technological University, Professor, master's tutor. Research direction: Civil Engineering and engineering cost management. Work unit: Qingdao Technological University.

Jiang Zhenyao (1992-), female, master's degree graduate student. Research direction: civil engineering construction cost management. Work unit: Qingdao Technological University.

Contributor contact: Wei Xiaozhao Tel: 18766215697

Contributor mailbox: 1537726628@qq.com

Mailing address: Qingdao Economic Development Zone No. 2 Changjiang River (old campus of Qingdao Technological University)